



## **WISP**

### **Western Interconnection Synchrophasor Program Communication and Data Quality**

**Dan Brancaccio**

NASPI Work Group Meeting


October 17-18, 2012

**NASPI** *North American  
SynchroPhasor Initiative*

# *Acknowledgement and Disclaimer*

---


- Acknowledgment: This material is based upon work supported by the Department of Energy under Award Number DE-OE0000364.
- Disclaimer: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



# *Communication Design Goals*

---

- Edge router to edge router < 30ms latency
- Backbone network 99.9999% available
- Last mile (local loop) 99.99% availability
- Source PDCs: Dual redundant PDCs at two separate physical locations
- Destination PDCs: Dual redundant PDCs at two separate physical locations



# *PMUs and PDCs*

---

Total existing or planned PMUs	484
Total existing or planned PDCs:	59
PMUs currently deployed:	200
PMUs currently streaming data:	90

Class A data 50/50 mix sample rate 30Hz and 60Hz

# *High Availability and Disaster Recovery*

---

- Redundant PDCs at each collection site location
  - Manual switchover between PDCs at each site
  - Both sites active
  - Disaster recovery plan in development
- Redundant PDCs at some source locations

# Archives

---

- Storage duration and capacity:
  - All Data On-Line – 15 months
  - Disturbances – 7 years
  - 100+ TB
- Redundant Archives at each archive location



# Communications

---

- Dedicated, private wide-area network (WAN);
- Provided by Harris Corporation:
  - All data on WAN is encrypted using GET-VPN WECC control keys;
  - WAN from RCs up to TOs/ISOs edge routers under contract to WECC;
  - Centralized management;
  - Core network deployment complete: Nov. 2011;
  - Final PDC to PDC communications testing: Nov. 2012; and
- Peer-to-peer communication is occurring; and
- Will facilitate NASPInet phasor gateway demonstration – March 2013.

# *Performance monitoring*

---

- Edge to edge router performance tracked by Harris
  - Notification of outages is fully automated
- Full end to end monitoring presently being handled by openPDC
  - Working with vendor to develop more accurate monitoring
- Participant PMU and / or PDC outages presently handled through email notification
  - Workflow in place to track outage

# *PMUs (cont.)*

---

- Data Quality:
  - 95 percent of PMUs delivering quality data some issues with older PMUs;
  - A small number of PMUs have timing issues (one is convinced it is 2034); and
  - In all cases so far, timeliness issues have been PMU related not communication system related, even when communications are over serial connections.

# Communications

---

- Data flows and speeds:
  - PMU to PDC communication controlled by each Participant — latency varies among Participants.
  - PDCs to RCs for centrally processed applications:
    - Edge router to edge router latency requirement is 30 ms average over 10 min, experiencing 19 ms; and
    - Jitter requirement is 2 ms average over 10 min, experiencing 1.4 ms.
    - WAN availability 99.99 percent (measurement beginning May 2012).
  - Expecting 2100 phasor measurements initially — WAN capable of 10X this volume limited only by ‘last mile’ connection.