

DOE/OE Transmission Reliability Program

Real Time Applications Using Linear State Estimation Technology (RTA/LSE)

DOE Grant Award #DE-OE0000849

Ken Martin & Lin Zhang, Principal Investigators
Electric Power Group

NASPI

Oct 23, 2018

Philadelphia, PA



Electric Power Group



Acknowledgement and Disclaimer

- Acknowledgment: This material is based upon work supported by the Department of Energy under Award Number DE-OE0000849.
- Disclaimer: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



Electric Power Group



Presentation

- Introduction & participants
- Project objective & approach
- Overview of application developments
- Status & schedule
- Planned activities



Electric **P**ower **G**roup



Introduction

- Project: Real Time Applications Using Linear State Estimation Technology
 - DOE Grant Award DE-OE0000849
- Primary recipient: Electric Power Group, LLC
 - Principal Investigators: Ken Martin & Lin Zhang
- Project Partners (host site & cost share):
 - Bonneville Power Administration
 - Project lead – Tony Faris/Thong Trinh
 - New York Power Authority
 - Project lead – Atena Darvishi/Alan Ettlinger
- Project host site - Duke Energy
 - Project lead – Megan Vutsinas, Tim Bradbury, Evan Phillips



Electric Power Group



Advisors & observers

- Project Advisors
 - Anjan Bose – Washington State University
 - Ian Dobson – Iowa State University
 - Dejan Sobajic – Grid Engineering
 - Anurag Srivastava – Washington State University
- Project Observers
 - Dominion Virginia Power (Dominion) - Kyle Thomas
 - Peak Reliability - Hongming Zhang
 - PJM - Emanuel Bernabeu, Ryan Nice



Electric Power Group



Project Objective

- Develop Real Time Applications Using Phasor Data and Linear State Estimator Technology
 - Provide operators with actionable intelligence on contingencies, voltage margins, & phase angle limits
- Applications include
 - Real Time Contingency Analysis
 - Voltage Stability Monitoring
 - Area Angle Limit Monitoring




Electric Power Group



Project approach

- Implement 3 applications to monitor power system
- Test with simulated and recorded data
- Demonstrate at host utilities



Electric Power Group



ENHANCED LINEAR STATE ESTIMATOR (*e*LSE)




Electric **P**ower **G**roup



eLSE Inputs

- Network Model (CIM format)
 - Converted into eLSE format model
- PMU Data (C37.118)
 - Real-time or recorded
- Topology Info (Breaker status)
 - From EMS or recorded




Electric Power Group



Flow Chart of *e*LSE Engine

- *e*LSE input interface processes inputs and send them to *e*LSE core modules
- *e*LSE core modules include:
 - Topology Process
 - Observability Analysis
 - Linear State Estimation
 - Bad Data Detection & Identification



Electric Power Group



REAL-TIME CONTINGENCY ANALYSIS (RTCA)



Electric Power Group



RTCA operation

- Tests what can happen next based on the current system
 - Uses a pre-made list of contingencies such as line outages, transformer failure, RAS actions, etc.
 - Checks for low voltage or excessive power flow caused by the outage
- Uses a solved case from the LSE
- Applies each contingency, checks for violations
 - Check power flow and bus voltage limits
 - Rank and list violations
 - Send alerts based on violation level
- Manual operation allows testing user specified cases
 - Special conditions, pre-study before switching




Electric Power Group



RTCA Challenge – getting good results with small number of measurements (observability)

- Entire Network = G
- LSE observable subnetwork = S
- Systems connected by lines on boundary busses B_i
- P_{s-inj} = Power Injection at Boundary Buses



Approach with 2 methods:

Method 1 – consider only the observable subsystem S


Method 2 – consider the whole system but update observable portion S



Electric Power Group



Method 1




- Use only the subsystem that is covered by PMU measurements (this portion is called ‘observable’)
- External System is removed and its effect is represented by constant Power Injections (P & Q)
- Apply contingencies only to subsystem S



Electric Power Group



Method 2




- Use the entire system G
- Update the observable subset S with measurements from the LSE
- Use the load flow program to adjust the whole system to the observable system
- Apply contingencies to any part of the system (primarily subsystem S)



Electric Power Group



Method 2 Results – Contingency Line 16-17



Highlighted – Buses/Lines in Subnetwork S

Vmag (pu)				Power (MW)				
Contingency 16_17								
Bus Results				Branch Results				
Bus No	Scaled System	Full System	% Error	From Bus	To Bus	Scaled System	Full System	% Error
1	1.04923587	1.052979209	-0.355499848	1	2	-90.78242352	-85.25989106	6.477292423
2	1.05218021	1.06171797	-0.898332755	1	39	90.78242352	85.25989106	6.477292423
3	1.041905853	1.058670871	-1.583591123	2	3	423.115656	352.9883521	19.86674729
4	1.035508921	1.0571593	-2.04797698	2	25	-203.3053485	-188.4837451	7.863597665
5	1.05470734	1.071598385	-1.576247728	2	30	-275	-250	10
6	1.056629554	1.072330031	-1.464146002	3	4	-118.7364212	-96.37446678	23.20319392
7	1.042342825	1.059207037	-1.592154449	3	18	153.323605	125.9258513	21.75705261
8	1.03981934	1.056665055	-1.594234154	4	5	-256.5929558	-189.7680978	35.21395786
9	1.046141916	1.053120786	-0.662684656	4	14	-485.4783458	-406.7164714	19.36530237
10	1.044515506	1.058894016	-1.357879958	5	6	-619.6029206	-522.2469011	18.64176107
11	1.047033338	1.062112774	-1.419758511	5	8	362.3814279	332.1413506	9.104580701
12	1.028982864	1.046919127	-1.713242536	6	7	495.5005047	444.8030266	11.39773678
13	1.039967646	1.056147984	-1.532014230	6	11	-437.4537944	-403.7312554	8.35271941
14	1.032597618	1.052484955	-1.889560147	31	6	678.3410623	563.7939983	20.317184
15	1.014522239	1.034296519	-1.911867393	7	8	236.8932233	209.880234	12.87067425
16	1.025213515	1.041943999	-1.605698914	8	9	23.81361083	18.98227286	25.45197352
17	1.038753736	1.057691257	-1.750458289	9	39	23.79344621	18.97309836	25.40622385
18	1.038264852	1.056873646	-1.760739702	10	11	435.7747427	401.5335539	8.527603615
19	1.044659973	1.053572273	-0.845912495	10	13	279.2252573	248.466447	12.37948233
20	0.986500768	0.992901562	-0.644655527	10	32	-715	-650	10
21	1.022396001	1.038918058	-1.590313749	12	11	3.838258963	4.035430282	-4.886004842
22	1.043347599	1.053627441	-0.975661877	12	13	-12.08825896	-11.53543028	4.92444092
23	1.037240403	1.048755516	-1.097978715	13	14	266.7976101	236.6816178	12.72426331
24	1.030867715	1.046580913	-1.501383967	14	15	-201.1559048	-171.7125885	17.1468595
25	1.057086774	1.065654822	-0.804017179	15	16	-586.0332429	-492.3732826	19.02214512
26	1.047644273	1.064021159	-1.539150419	16	17	0	0	
27	1.035675979	1.055233488	-1.853382129	16	19	-539.5111385	-451.4357074	19.51007189
28	1.045186671	1.056303402	-1.052418357	16	21	-394.2090448	-329.6866614	19.57082008
29	1.046000606	1.054182869	-0.776171096	16	24	-50.61302554	-42.69641942	18.54161597
30	1.0475	1.0475	0	17	18	36.52633923	32.23689631	13.30600466
31	0.982	0.982	0	17	27	-36.52633922	-32.23689631	13.30600461
32	0.9831	0.9831	0	19	20	192.5420128	174.6968819	10.21491094
33	0.9972	0.9972	0	19	33	-691.6457851	-629.1367816	9.935677788
34	1.0123	1.0123	0	20	34	-555.7265963	-505.5193695	9.931810703
35	1.0493	1.0493	0	21	22	-698.1478253	-604.5058795	15.49065923
36	1.0635	1.0635	0	22	23	13.07103266	42.76601306	-69.43593354
37	1.0278	1.0278	0	22	35	-715	-650	10
38	1.0265	1.0265	0	23	24	424.6637154	353.8234394	20.02136324



Electric Power Group



Decision & next steps

- Method 2 selected
 - Both methods produced high errors at boundary due to limited observability
 - Method 2 gave better results and also allows testing contingencies near boundary and externally; drawback is longer computation time
 - Testing with IEEE 300 bus test system confirmed improvement on a bigger system and advantages of Method 2
- Testing for deployment at BPA
 - WECC Planning Case 2020 HS (~ 20,000 Buses)
 - Subnetwork – 500 kV BPA System
 - Buses – 162 and Branches – 196



Electric Power Group



VOLTAGE CORRIDOR STABILITY LIMIT MONITORING




Electric Power Group



Methodology: Single Line Equivalent for a Transmission Corridor



- The PMU measurements at both ends of a transmission corridor are required
- Complex power is computed from the complex V & I measurements
- Using the complex power through the system and current flow in and out of the corridor, the voltage across the corridor can be computed
- The index is simply the voltage across the system divided by the load voltage
- Reactive support has to be considered



Electric Power Group



VSI reaction to loss of 2 Palo Verde Units



Next steps: determine threshold & determine reactive support



Electric Power Group



AREA ANGLE LIMIT MONITORING




Electric Power Group



Area-angle application

- Power flow creates a phase angle
- Higher angles result from
 - Higher power flow
 - Higher impedance (fewer lines carrying flow)
- Angle can indicate excessive stress or a lost transmission line
- Area angle indicates transmission failure or overloads

Power
flow
into
area



Power
flow
out of
area




Electric Power Group



Methodology: reduce area & relate to angle

- Select an area with a distinct power flow through it, that has PMU measurements at all busses on border of area
- Determine a weighting for each boundary bus based on the network admittances; this uses the Kron reduction on the base case to determine the weighting. This effectively reduces the area to a single line equivalent
- The maximum allowed power flow is determined by studying single line outages; the area angle threshold is given by the worst case outage




Electric Power Group



Challenges

- With limited PMU coverage, it is difficult to find an area where the boundary is completely monitored by PMUs
- The area needs to have a distinct power flow through it to cause angle changes reflected by power flow
- With a large meshed grid, there may be many exceptional outages (ie, outages where line limits are exceeded but the angle change doesn't exceed a threshold)



Electric Power Group



Project status

- Presented paper on RTCA development at the NAPS conference in September 2018
- Project extended 1 year to March 14, 2020
- RTCA and voltage corridor applications have been turned over to the EPG development team
 - User interfaces will also be developed
- We continue to resolve issues in Area angle app



Electric Power Group



Extended Project Timeline

Task	Deliverable	Completion Date	Documentation & notes
1	Project Management Plan	4/12/2017	Project management plan document
2	Research, Design & Development of Prototype		
2.3	<i>Real time applications prototype, and development and testing</i>	10/1/2018	Test cases and test results
2.3A	<i>Completion and testing of deployable applications</i>	1/31/19	Documented test results
2.4	<i>Prototype Demonstration for DoE and all the participants</i>	3/16/2019	Demonstration at EPG
3	Deployment, Testing & Acceptance		
3.1	<i>Factory Acceptance Test</i>	5/4/2019	Test cases and test results
3.2	<i>Site Acceptance Test</i>	8/31/2019	Test cases and test results
4	Demonstration at utility host site, training and a report	11/7/2019	Demonstration, training and report
5	Marketing and Outreach		
5.1	<i>Marketing Plan</i>	2/1/2020	Marketing plan
5.2	<i>Outreach</i>	3/14/2020	Industry presentations & briefing documents



Electric Power Group



Looking Forward

- Planned next steps
 - Application Implementation in operational code
 - Operational code testing in December 2018
 - Develop area angle application
 - Adapt applications for test site deployment
 - NYPA – November-December 2018
 - Duke – January-February 2019
- Project roadmap
 - FY 2019: Complete application development & deploy at host sites
 - FY 2020: Host site demonstrations with real-time operation & produce commercialization plan



Electric Power Group



Questions?



Electric Power Group

